



german  
brand  
award  
19  
winner

## Infrared glass picture heater – Datasheet

### Essential performance:

Surface area:	ESG toughened safety glass
Back side:	Steel sheet powder-coated
Scope of application:	direct heating
Surface temperature:	approx. 90°C till 100°C
Voltage:	220-240 VAC 50Hz
Colour:	Print on frameless glass front
Protection class:	IP 54 / protection level 1
Temperature monitors:	1-3 pieces, size related
Installation height:	44 mm incl. assembly <i>(within the scope of delivery)</i>

### Sizes and power

Item no.	Size	Power	Weight
GB-250	60 x 30 cm	250* +/- 8%	4,1 kg
GB-350	90 x 30 cm	350* +/- 8%	6,2 kg
GB-420	60 x 60 cm	420* +/- 8%	8,0 kg
GB-540	80 x 60 cm	540* +/- 8%	10,1 kg
GB-750	90 x 70 cm	750* +/- 8%	13,0 kg
GB-820	170 x 40 cm	820* +/- 8%	14,1 kg
GB-900	100 x 80 cm	900* +/- 8%	16,3 kg
GB-930	130 x 60 cm	930* +/- 8%	15,9 kg
GB-1150	120 x 80 cm	1150* +/- 8%	20,0 kg
GB-1250	160 x 60 cm	1250* +/- 8%	22,1 kg

*\*rated power within 230 volts*

Packaging:	carton composed of 100% recyclable material
Installation:	wall mounting
Heat regulation:	wireline or radio room thermostat <i>(not part of the scope of delivery)</i>

