




DIGELHEAT
INFRAROT HEIZUNGEN



german
brand
award
19
winner

Infrared mirror heater - Datasheet

Essential performance:

Surface area:	Mirror (ESG safety glass)
Back side:	Steel sheet powder-coated
Scope of application:	direct heating
Surface temperature:	approx. 90°C till 100°C
Voltage:	220-240 VAC 50Hz
Protection class:	IP 54 / protection level 1
Temperature monitors:	1-3 pieces, size related
Installation height:	44 mm incl. assembly (within the scope of delivery)

Sizes and power:

Item no.	Size	Power	Weight
SH-250	60 x 30 cm	250* +/- 8%	5,0 kg
SH-350	90 x 30 cm	350* +/- 8%	7,5 kg
SH-420	60 x 60 cm	420* +/- 8%	12,5 kg
SH-540	80 x 60 cm	540* +/- 8%	13,0 kg
SH-750	90 x 70 cm	750* +/- 8%	16,2 kg
SH-900	100 x 80 cm	900* +/- 8%	20,3 kg
SH-930	130 x 60 cm	930* +/- 8%	19,8 kg
SH-1150	120 x 80 cm	1150* +/- 8%	24,4 kg
SH-1250	160 x 60 cm	1250* +/- 8%	25,0 kg

*rated power within 230 volts

Packaging:	carton composed of 100% recyclable material
Installation:	wall mounting
Heat regulation:	wireline or radio room thermostat (not part of the scope of delivery)

